Competitive Problem Based Learning in an Environmental Engineering Laboratory Course

A. Jason Hill¹, Ph.D., P.E. and Zane W. Mitchell², Jr., Ph.D., P.E., PMP, LEED AP University of Southern Indiana

Abstract

The Problem-based learning (PBL) pedagogical approach to instruction has become widely used in engineering courses. This paper describes implementation of the PBL approach to an environmental engineering laboratory course. The course serves as an elective option for students pursuing a Bachelor of Science in Engineering degree. The PBL approach was used for the laboratory component to provide an applied context to traditional experiments implemented in this course. Two problems were defined and used to motivate the design of weekly laboratory sessions. The first problem was to design a treatment system to produce drinking water from river water. Laboratory sessions were used to conduct a variety of relevant water quality tests and examine different treatment methods. Relevant drinking water regulations were presented to provide a treatment goal. A water treatment competition was designed to provide a creative outlet for presenting the final treatment schemes. The competition required each team to integrate experience from previous laboratory sessions. Each team was scored based on the quality of the treated water, efficiency of treatment, experimental techniques, and the final design report. The second problem concerned evaluating the performance of an activated sludge wastewater treatment plant. Students visited a local plant and obtained samples for testing. Both problems required extensive use of traditional experimental procedures and reinforced many of the course lecture topics. Students were required to maintain a laboratory notebook and submit two reports detailing the two problem solutions. The PBL approach was implemented in lecture using a series of class problem set packets. Interactive problem solving sessions were conducted to solve the problems with short periods of traditional lecture interjected as needed. Lecture material was introduced as needed to solve the problem sets. Student feedback regarding the lecture and laboratory components of the course was very positive. Advantages of this approach include greater connectivity between lecture and laboratory topics and a greater focus on experimental design, a requirement of ABET outcome 3b.

1. Introduction

Problem-based-Learning (PBL), a pedagogical instructional approach founded in the medical sciences, has found widespread use in engineering (Johnson 1999, Quinn and Albano 2008, Brodeur et al. 2002) and general science curriculums (Ram 1999). The PBL approach requires the instructor to define a problem and use it to motivate learning. This approach is often referred to as a student-centered approach since the students strategy for solving the problem is allowed to dictate how a course or activity proceeds. With this approach, the instructor must be prepared to accommodate a wide variety of paths to a viable solution. The PBL approach is well suited for engineering courses with significant applied design content and is a staple in the full spectrum of engineering design ranging from introductory engineering courses (Mitchell et. al, 2001) to capstone design courses (Dutson et al. 1997.)

Application of the PBL approach to laboratory courses has also been reported in the literature (Kelly and Finlayson 2007, Macias-Guarasa et al. 2005). Kelly and Finlayson (2007) implemented the PBL approach in a freshman level chemistry laboratory. They note that traditional laboratory activities consist of teacher-structured experiments where step-by-step procedures are followed that requires no significant student engagement. This type of laboratory has been referred to as a "recipe-lab" (Domin 1999).

The objective of this paper is to describe implementation of a PBL instructional approach for both the lecture and laboratory component of an introductory environmental engineering course taken by upper level engineering students. Learning experimental measurement procedures for constituents in water and wastewater has traditionally been the focus of laboratory investigations in this course. A standard laboratory activity consists of following a specific procedure (i.e., a "recipe-lab") from the reference "*Standard Methods for the Examination of Water and Wastewater*". While there is certainly value in this type of instructional model, the drawbacks to this approach include a lack of connectivity with lecture material and a lack of student engagement in experimental design.

The approach described herein is a hybrid approach consisting of traditional experiments implemented within an overall PBL framework. A unique aspect of this approach is the use of an end-of-semester competition where student teams are required to assimilate knowledge from earlier experiments while solving a design problem. Competitions of this type are common elements of regional student conferences sponsored by professional organizations (e.g., ASCE). Interactive problem solving sessions centered around class problem sets are used to implement PBL in the lecture component of the course.

2. Course Overview

The environmental engineering course (ENGR428) serves an elective option for students pursuing a Bachelor of Science in Engineering (BSE) at the University of Southern Indiana, an ABET accredited program. It is typically taken by students with a declared emphasis in civil engineering, although it can be taken by any engineering student who has met the prerequisites. Course prerequisites include one semester of general chemistry and fluid mechanics. An approximate topical breakdown is provided in Table 1. Fundamental principles comprise 40% of the course, including a significant environmental chemistry component. The remainder of the semester is devoted to applications in the various subfields of environmental engineering, with an emphasis on water and wastewater treatment. The course is 4 credit hours with 3 lectures (50 mins) and a single laboratory session (2 hrs and 50 mins) each week. The PBL approach was implemented during the Fall 2012 semester with a total enrollment of 7 students.

Торіс	Percentage of Course
Environmental Chemistry	
Units of Concentration	
Stoichiometry, Theoretical Oxygen Demand	20
Kinetics	
Equilibrium	
Ecological and Biological Principles	
Biochemical Oxygen Demand	5
Nutrient Cycles	5
Microbial Growth	
Mass and Energy Balances	15
Water Treatment	15
Wastewater Treatment	15
Water Quality Management	
Types of Pollutants and Their Sources	10
Dissolved Oxygen Sag Model	
Introduction to Hydrology	10
Solid and Hazardous Waste Management	5
Air Pollution	5

Table 1.	Content of ENGR428 Environmental Engineering

3. Course Implementation of PBL

3.1. Lecture Component

Lecture time was devoted primarily to interactive problem solving sessions with brief periods of traditional lecture interjected as needed. Rather than using a single complex design problem as with capstone projects, a collection of simpler problems were used. Each lecture topic was organized around a "class problem set" packet consisting of problem statements and blank space for students to record the solutions and relevant background information (equation development, definitions, etc.). Problems were selected or designed to include not only relevant technical data, but also a real world context. All problems were solved in class with the students completing all calculations and providing input on the general solution strategy.

To illustrate the technique, consider the following problem from one of the class problem sets on "Equilibrium", which included a total of seven problems. It is a textbook problem adapted from Mihelcic (1999) and concerns the removal of Atrazine from drinking water.

<u>Example Class Problem</u>: Atrazine, a widely used herbicide, contained in agricultural runoff has contaminated a reservoir that is used as a source of drinking water. The atrazine concentration in the reservoir was measured to be 0.012 mg/L (12 ppb). In order to treat the reservoir water so that atrazine is removed below the drinking water standard of 0.003 mg/L (3 ppb), powdered activated carbon is added to a contact basin (a mixing tank) to adsorb the atrazine. The PAC is then removed in a settling tank located down gradient. Assume that the city treats 10^6 gallons of drinking water per day, and that the Freundlich isotherm parameters for atrazine and this particular type of PAC are K=287 mg/g (L/mg)^{1/n} and 1/n=0.335. What concentration is lowered to the drinking water standard? What mass of PAC must be placed in the contact basin daily to ensure that atrazine is removed to concentrations that satisfy the drinking water standard?

At this point in the course, the students have had no exposure to the phenomenon of adsorption or isotherm models, a type of equilibrium model. Before beginning the problem solution, background information on the use of atrazine and drinking water standards was provided. This included displaying a map showing the measured atrazine concentrations in Indiana and a brief discussion of drinking water regulations. A sample of activated carbon was passed around the class while discussing its unique properties. Students were then asked how to compute the total mass of Atrazine that must be removed daily to meet the drinking water standard. This requires a simple mass balance and is a prerequisite skill for the course. A formal definition of adsorption was written on the board and commonly used isotherm equilibrium models were presented. Students then completed the remaining calculations.

Additional problems from the same set addressed acid mine drainage treatment, ammonia removal from wastewater, oxygen solubility in water, and a hazardous waste spill. The final result from the student perspective was a packet of solved problems with all relevant traditional lecture material included. Over the course of the semester, 10 class problem set packets were distributed to students and completed. Each class problem set was accompanied by a homework assignment.

3.2. Laboratory Component

All laboratory activities were devoted to the solution of two problems. Both problems were presented to the class and used to motivate laboratory activities throughout the semester. A team format was followed for all activities. Each team (2 total) was required to maintain a standard laboratory notebook with meticulous records of all activities (raw data, measurement procedures, interpretation, etc.). The two problem statements as presented to the students are provided below.

<u>Problem Statement #1</u>: Our basic goal is to design a treatment system to treat Ohio River water, producing a final product that is in compliance with federal drinking water regulations. To achieve this, we will need to characterize the source water (i.e., water quality parameters) and explore different treatment system designs. Each team will design their own treatment system consisting of conventional treatment (coagulation, flocculation, and sedimentation), filtration, and disinfection. We will visit the Evansville water treatment plant to see a large plant in operation and get some ideas for your own treatment systems. Finally, we will conduct a team competition to see which teams' treatment system produces the highest quality water.



Figure 1. Schematic for problem concerning drinking water treatment

<u>Problem Statement #2</u>: Our basic goal is to visit and evaluate the performance of a wastewater treatment plant (WWTP). We will tour the WWTP located near the Ohio River on the east side of Evansville, IN. The WWTP is a conventional activated sludge system. Influent and effluent samples will be collected for testing. The samples will be tested for biochemical oxygen demand (BOD) and solids content (total, suspended, and dissolved). We will also collect samples from the aeration basin and compute the sludge volume index (SVI) and sludge density index (SDI). These measures are indicators of settleability and are good performance indicators. The performance of the plant will be evaluated by comparison of measured values with discharge limits set by the NPDES

(National Pollutant Discharge Elimination System) permit and recommended ranges found in design guidance documents.

Both teams were required to submit two comprehensive reports detailing their solutions to each problem. General guidance on report content was provided; both were required to include an overview of the treatment plants visited and a summary of testing procedures and results.

3.2.1. Laboratory Activities

The solution to both problems required extensive use of traditional experimental procedures (techniques, equipment, etc.). The semester began with presentation of problem #1 (drinking water production) using the three basic components illustrated in Figure 1. An interactive brainstorming session was conducted to allow the students input on each aspect of the problem. A number of relevant discussion topics emerged, including specific contaminants of concern (herbicides, hydrocarbons, etc.), disinfection of pathogens, and treatment system design. Typical flow diagrams for surface and groundwater treatment were drawn on the board to aid the discussion. The first meeting concluded with a demonstration of conventional water treatment (coagulation, flocculation, and sedimentation) using standard jar testing equipment.

Beginning with the second meeting, laboratory time was devoted to completion of the experiments described in Table 2. The connection of the various activities to the main problem was emphasized throughout the semester. Most experiments served a secondary role of reinforcing specific lecture materials (unit conversions, stoichiometry, kinetics, etc.). Relevant drinking water regulations were presented throughout the semester to establish a treatment goal (Figure 1). A field trip to a water treatment plant was scheduled early in the semester. Students were required to obtain river samples each week for testing and log water quality parameters such as turbidity, pH, conductivity, and dissolved oxygen concentration in their laboratory notebooks. Additional relevant data was obtained online from the Ohio River Valley Water Sanitation Commission (ORSANCO) website. Approximately 80% of the laboratory time was devoted to the solution of problem #1.

The second problem was introduced to the students after the course mid-term exam. Considerably less time was required to solve problem #2 due to some overlap in procedures and previous student exposure to wastewater treatment in lecture. A tour of a local wastewater treatment plant was completed first. Samples were obtained and returned to laboratory for testing. A second trip to the plant was necessary later in the semester. A description of the laboratory experiments completed to solve problem #2 is given in Table 3.

Overall, the activities detailed in Table 2 and 3 required full use of the scheduled laboratory sessions.

Experiment	Description
Turbidity	Turbidity is a measure of the "cloudiness" of a water sample and is caused by the presence of suspended material. Calibration and use of a turbidimeter was demonstrated.
Hardness	Water hardness is defined as the total concentration of multivalent cations in a sample (expressed in mg/L as CaCO ₃). Students determined water hardness by titration with a chelating agent (EDTA).
Water Treatment	Students toured the water treatment plant located in Evansville, IN.
Plant Tour	The plant uses a conventional treatment train consisting of course screening, coagulation, flocculation, sedimentation, granular filtration, and disinfection.
Alkalinity/Acidity and pH	The ability of water to resist changes in pH as an acid or base is added is referred to as buffering capacity. Alkalinity and Acidity are measures of this buffering capacity. Calibration and use of a pH meter were demonstrated. Students used titration to determine the alkalinity and acidity. Water deficient in alkalinity may experience pH fluctuations during treatment.
Disinfection and "Ct" Tables	Water for drinking and cooking purposes must be made free from disease-producing microorganisms (pathogens). Students evaluated the use of sodium hypochlorite as a disinfectant. Total, free, and combined chlorine were determined for a range of applied chlorine dosages. The breakpoint chlorine dosage was determined.
Total Coliform	The microbial quality of water is based on testing for indicator microorganisms (those whose presence is evidence that the water has been polluted with feces and indicates the possible presence of pathogens). Students used the membrane filter technique to detect the presence of a group of indicator microorganisms known as coliform bacteria. Positive results indicate inadequate disinfection.
Jar Test	Students conducted a standard jar test to conduct conventional water treatment operations (coagulation, flocculation, and sedimentation). Aluminum sulfate was used as a coagulant.
Solids and Conductivity	Solid matter in water is either dissolved or suspended. Students determined total solids, suspended solids, and dissolved for river water samples. For drinking water, dissolved solids should be less than 500 mg/L to avoid taste problems. The use of a conductivity meter was demonstrated.
Iron and Manganese	Iron and manganese in high concentrations can cause offensive taste, appearance, and staining. Students determined the concentration of both compounds and evaluated the use of potassium permanganate as a pre-oxidant.
Taste and Odor/THM formation	Students were exposed to taste and odor and trihalomethane issues during the treatment plant tour. Students completed jar testing to determine potassium permanganate demand.

Table 2. Summary of experiments completed to solve problem #1 (drinking water production)

Table 3. Summary of experiments completed to solve problem #2 (wastewater treatment plant performance)

Experiment	Description and Relevance		
Wastewater Treatment Plant	Students toured the Wastewater Treatment Plant		
Tour	(WWTP) located near the Ohio River on the east side		
	of Evansville, IN. The WWTP is a conventional		
	activated sludge system. Students obtained samples for		
	testing. Sample locations included influent to plant,		
	influent to secondary treatment, aeration basin, and		
	plant effluent.		
Biochemical Oxygen Demand	The BOD test is performed to characterize the strength		
(BOD)	of a wastewater. Discharge permits (NPDES permits)		
	for wastewater treatment plants typically require the		
	BOD to be at or below 30 mg/L. Students determined		
	the 5-day BOD and estimated the ultimate BOD.		
Solids Analysis	In addition to total, suspended, and dissolved solids,		
	the volatile and fixed fractions were also determined.		
Settling	The settleability of primary and secondary sludge was		
	evaluated by settling in an Imhoff cone. The sludge		
	volume index (SVI) and sludge density index (SDI)		
	were determined.		
Dissolved Oxygen and	The transfer of oxygen to water is of fundamental		
Transfer in Aerated Systems	importance in the biological treatment of wastewater.		
	Students used a membrane probe and the Winkler-		
	Azide method to determine dissolved oxygen		
	concentration. The kinetics of oxygen transfer was		
	studied using a laboratory scale aeration basin.		
	Kinetics data was collected and a mass transfer rate		
	coefficient determined.		

3.2.2. End-of-Semester Laboratory Competition

A water treatment competition was held during the last laboratory session of the semester. The purpose was to provide a creative and fun outlet for each team to present their solutions to problem #1. Students were provided with competition details and all required materials 2 weeks before the actual event. The competition was designed by the instructor to require both teams to use results and procedures from earlier experiments (Table 2). Each team was required to make several design decisions and work effectively as a team to minimize the total treatment time.

Each team was provided with the following supplies:

- Two coagulants (A and B): polyaluminum chloride and aluminum sulfate
- Potassium Permanganate, KMnCl₄

- Chlorox Bleach (5.25% Sodium Hypochlorite)
- Powdered Activated Carbon (PAC) solution (concentration not specified)
- Sodium Hydroxide (0.02 N)
- Sulfuric Acid (0.02 N)
- Sodium Bicarbonate (NaHCO₃) powder
- Filter media: anthracite coal, sand, and gravel
- Filter materials: 3 ft section of cylindrical pipe and perforated cap

Students constructed granular filters and developed flexible chemical dosing schemes prior to the competition. Design variables also included jar test operational parameters (mixing time and speed). A flexible treatment scheme was necessary since the quality of the water to be treated (turbidity, pH, etc.) was not known ahead of time. On the day of the competition, each team was provided with 35 L of raw water and required to produce 6 L of treated water. Each team was scored based on the quality of the treated water, efficiency of treatment (teamwork), experimental techniques, response to questions by the instructor, and the final design report. The two designs varied significantly; Table 4 summarizes the two designs and how each performed.

Parameter	Team A	Team B
Initial Turbidity (NTU)	55	72
Initial pH	7.8	7.8
Coagulant	В	В
Coagulant Dosage (ppm)	190	70
Potassium Permanganate Dosage (ppm)	0.3	0.3
Turbidity Before Filter (NTU)	1.20	2.40
Powdered Activated Carbon Dosage	0.5	0.1
(mL/L)		
Filter Flow Rate (Lpm)	1.0	0.4
Filter Overflow Rate (m/day)	734	315
Applied Chorine Dosage (ppm)	1.25	4
Chlorine Contact Time (min)	39	8
Final Turbidity (NTU)	0.93	0.7
Final pH	7.15	7.08
Free Chlorine Residual (ppm)	0.60	1.54
Total Treatment Time (hrs)	3.2	2.18

Table 4. Comparison of team designs for the drinking water competition

4. Course Evaluation

A survey was administered at the end of the course and completed by 6 of the 7 students. The survey asked the students to evaluate how well 15 course performance outcomes were achieved using a scale ranging from 0 to 100. The outcomes addressed specific competencies related to the course content in Table 1. Average scores, as a percentage, are shown in Figure 2. For comparison, a classroom composite score, derived from specific assignment and exam questions, was computed for 13 of the outcomes. Graded material was not available for 2 of the outcomes. All student scores were above 80%, indicating the students felt they achieved the course outcomes. Classroom composite scores were within 10 percentage points of the student values. Students were also asked to score their overall satisfaction with the course and laboratory. Scores averaged 95% for the course and 90% for the laboratory.



Figure 2. Assessment of 15 performance outcomes including both a self-assessment score and a composite score derived from graded assignments and exams

Students were also given the opportunity to provide written comments regarding the course. The following comments [unedited] specifically addressed the use of in-class problem sets and the laboratory format:

I actually really do like your teaching style with the use of class problem sets and working through these during lecture to learn the material. I feel this is a great way for me to learn.

This is an excellent course, and I feel that I have learned more in this course than any other single course. I really like in class problems and the lab format.

The lab activities reinforced ideas from lecture. I really like the format of lab such as not having weekly lab reports and a big report and project at the end. I feel this is a lot more manageable. I liked the field trips and gained a lot of knowledge from each one. Great class and great lab!

These comments are compelling and suggest the PBL approach was successful. On the negative side, informal feedback by select students suggested that time demands near the end of the course were excessive. This was anticipated and addressed by eliminating a third exam and increasing the weight of the laboratory portion of the course. Writing the final reports proved to be a daunting task for both teams. In the future, the instructor plans to require intermediate submissions and reviews prior to the final end-of-semester submission. An advantage of using a more substantial project report, rather than weekly reports, is that the final product is more representative of engineering consultancy reports.

5. Conclusions

A PBL instructional approach was shown to be effective for both the lecture and laboratory components of an introductory environmental engineering course. Compared to previous course deliveries, the instructor found considerably more enthusiasm displayed toward the laboratory component of the course. This is attributed primarily to the use of real world problems that provide an applied context to traditional laboratory experiments focused on measurement procedures. The laboratory problems provided greater connectivity with the lecture component of the course and included design components, thus shifting greater decision making responsibility to the students than with traditional "recipe-labs".

An end-of-semester water treatment competition was used successfully. The competition required students to integrate experience from previous laboratory sessions. Competitions are commonplace in engineering departments, but are often connected with student groups (ASCE, SAE, etc.) and participation is voluntary. These types of activities bring a fun and creative component to laboratory courses and are becoming more common in engineering curriculums (Mackechnie and Buchanan 2012). Laboratory instruction is a very important component of engineering curriculums and this study supports the use of a goal-driven competitive framework for delivery.

6. Acknowledgements

The authors would like to thank Tim Hall, water quality manager at the Evansville water treatment plant, for conducting a plant tour and donating chemicals and granular filter supplies. We would like to thank Joe Dickman, facility manager at the Evansville eastside wastewater treatment plant, for conducting the plant tour and assisting with sampling. Finally, we would like to thank the students whose hard work made this study possible.

7. References

APHA, AWWA, and WEF. (2005). "Standard Methods for the Examination of Water and Wastewater", 21st ed. American Public Health Association, Washington, D.C.

Brodeur, D.R., P.W. Young, and K.B. Blair. (2002). "Problem-Based-Learning in Aerospace Engineering Education", Proceedings of the American Society of Engineering Education Annual Conference and Exposition.

Domin, D.S. (1999). "A review of laboratory instructional styles", Journal of Chemical Education, 76:543-547.

Dutson, A.J., R.H. Todd, S.P. Magleby, and C.D. Sorensen. (1997). "A review of literature on teaching engineering design through project oriented capstone courses", Journal of Engineering Education, 86(1):17-28.

Macias-Guarasa, J., R. San-Segundo, J.M. Montero, J. Ferreiros, and R. Cordoba. (2005). "Tools and Strategies for Improving PBL Laboratory Courses with High Student-to-Faculty Ratio", Frontiers in Education Conference Proceedings, 2:F2C-7.

Johnson, P.A. (1999). "Problem-Based, Cooperative Learning in the Engineering Classroom", Journal of Professional Issues in Engineering Education and Practice, V125(1):8-11.

Kelly, O.C., O.E. Finlayson. (2007). "Providing solutions through problem-based learning for the undergraduate 1st year chemistry laboratory", Chemistry Education Research and Practice, 8(3):347-361.

Mackechnie, J.R. and A.H. Buchanan. (2012). "Creative Laboratory Model for Large Undergraduate Engineering Classes", Journal of Professional Issues in Engineering Education and Practice, V138(2):55-61.

Mihelcic, J. R. "Fundamentals of Environmental Engineering", John Wiley and Sons, New York, 1999.

Mitchell, Z. W. Jr., H. W. Washington, and C. D. Kuhl (2001). "Engineering and Construction Camp at the USAF Academy." Proceedings of the 31st ASEE/IEEE Frontiers in Education Conference, T1E1-E3.

Quinn, K.A., and L.D. Albano. (2008). "Problem-based learning in structural engineering education." Journal of Professional Issues in Engineering Education and Practice, V134(4), 329-334.

Ram, Preetha. (1999). "Problem-Based Learning in Undergraduate Education: A Sophomore Chemistry Laboratory", Journal of Chemical Education, V76(8):1122-1126.

Truax, D.D. (2007). "Restructuring the undergraduate laboratory instructional process", Journal of Professional Issues in Engineering Education and Practice, V133(3):192-198.

Bibliographic Information

A. Jason Hill¹, Ph.D., P.E.

Jason Hill is an Assistant Professor of Engineering at the University of Southern Indiana. He holds B.S., M.S. and Ph.D. degrees in Civil Engineering from Tennessee Technological University. His research interests include rainfall-runoff modeling and wetland hydrology. Email: <u>ajhill3@usi.edu</u>

Zane W. Mitchell², Jr., Ph.D., P.E., PMP, LEED AP

Zane Mitchell is an Associate Professor of Engineering at the University of Southern Indiana. He holds a B.S. degree in Civil Engineering from the United States Air Force Academy, an M.B.A. from Rensselaer Polytechnic Institute, and M.S. and Ph.D. in civil engineering from Virginia Tech. Dr. Mitchell is the Chairman of the Engineering Department at the University of Southern Indiana. Email: zwmitchell@usi.edu